

## Technical Data Sheet

### NUH ALUMINIUM PASTE NH 45

#### TYPICAL VALUE Aluminium Paste ( Water based)

	ACTIVE ALUMINIUM	D50 Malvern	45 µm % volume under	Non-volatile content
<b>NH 45</b>	Min 92 %	Mean. 20 µm	Min 90 %	75 ± 2 %

#### Characteristics:

- Fine aluminium paste
- Flake
- For the production of A.A.C. blocks with lower density (< 450).

#### Application:

- Aerated light weight concrete
- Plasters
- Chemical technical applications

Storage: The storage and transport should always take place in closed containers under cool conditions.  
shelf life : 3 months

#### HAZARDS IDENTIFICATION



H302 Harmful if swallowed.  
P264 Wash skin thoroughly after handling  
P280 Wear eye protection / face protection.

Halime KOŞLU

Quality Control and Environmental Management Systems Manager  
NUH YAPI ÜRÜN. A.Ş.

## Technical Data Sheet

### NUH ALUMINIUM PASTE NH 50

#### TYPICAL VALUE Aluminium Paste ( Water based)

	ACTIVE ALUMINIUM	D50 Malvern	45 µm % volume under	Non-volatile content
<b>NH 50</b>	Min 92 %	Mean. 22 µm	Min 85 %	75 ± 2 %

#### Characteristics:

- Fine aluminium paste
- Flake structure
- For the production of A.A.C. blocks with lower density (< 450).

#### Application:

- Aerated light weight concrete
- Plasters
- Chemical technical applications

Storage: The storage and transport should always take place in closed containers under cool conditions.  
shelf life :3 months

#### HAZARDS IDENTIFICATION



H302 Harmful if swallowed.  
P264 Wash skin thoroughly after handling  
P280 Wear eye protection / face protection.

Halime KOŞLU

Quality Control and Environmental Management Systems Manager  
NUH YAPI ÜRÜN. A.Ş.

## Technical Data Sheet

### NUH ALUMINIUM PASTE NH 60

#### TYPICAL VALUE Aluminium Paste ( Water based)

	ACTIVE ALUMINIUM	D50 Malvern	45 µm % volume under	Non-volatile content
<b>NH 60</b>	Min 92 %	Mean. 25 µm	Min 80 %	75 ± 2 %

#### Characteristics:

- Fine aluminium paste
- Flake structure
- For the production of A.A.C. blocks with lower density (< 450).

#### Application:

- Aerated light weight concrete
- Plasters
- Chemical technical applications

Storage: The storage and transport should always take place in closed containers under cool conditions.  
shelf life : 3 months

#### HAZARDS IDENTIFICATION



H302 Harmful if swallowed.  
P264 Wash skin thoroughly after handling  
P280 Wear eye protection / face protection.

Halime KOŞLU

Quality Control and Environmental Management Systems Manager  
NUH YAPI ÜRÜN. A.Ş.